

According to US Standard ANSI Z400.1-2004

Print date: 25-Jan-2011

PRODUCT AND COMPANY IDENTIFICATION

SDS Number: D0313648

Commercial Product Name: Lysol® Brand III I.C.™ Disinfectant Spray

Validation/Revision Date 25-Jan-2011

Product Identifier: EPA Reg. Number: 777-99-675

Formula Number: 1589-023 (0271639)

UPC Code(s) and Size: 36241-95029 (19 oz.)

Recommended use Disinfectant surface spray

Manufacturer: Reckitt Benckiser Inc.

Morris Corporate Center IV

399 Interpace Parkway (P.O. Box 225) Parsippany, New Jersey 07054-0225

Telephone: +1 973 404 2600

Distributor: Reckitt Benckiser Inc.

Morris Corporate Center IV

399 Interpace Parkway (P.O. Box 225) Parsippany, New Jersey 07054-0225

Telephone: +1 973 404 2600

Emergency Telephone Number: 1-800-228-4722 (U.S)

Transportation Emergencies: 1-800-424-9300 (U.S. & Canada) CHEMTREC

Outside U.S. and Canada (North America), call Chemtrec:703-527-3887



According to US Standard ANSI Z400.1-2004

2. HAZARDS IDENTIFICATION

Emergency Overview

CAUTION!

Causes moderate eye irritation.

DO NOT spray in eyes, on skin or on clothing.

Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, or using tobacco.

FLAMMABLE.

Contents under pressure.

Keep away from heat, sparks, and open flame.

Do not puncture or incinerate container.

Exposure to temperatures above 130° F may cause bursting.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Proportion (% w/w)	ACGIH - Occupational Exposure Limits - TWAs	OSHA PEL
Ethanol 64-17-5	30 - 60 %		TWA: 1000 ppm TWA: 1900 mg/m ³
n-butane	1 - 5 %	= 1000 ppm TWA 1 322 1	TWA: 1900 mg/m ³
106-97-8		Butane	TWA: 800 ppm
Propane	< 2.5 %	= 1000 ppm TWA 1 322 1	TWA: 1000 ppm
74-98-6		Propane	TWA: 1800 mg/m ³



According to US Standard ANSI Z400.1-2004

4. FIRST AID MEASURES

Inhalation Move to fresh air.

Skin ContactWash off immediately with soap and plenty of water removing all contaminated clothes and

shoes. If skin irritation persists, call a physician.

Eye Contact If in eyes, Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove

contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison

Control Center or Doctor for treatment advice.

Ingestion Clean mouth with water and afterwards drink plenty of water. DO NOT INDUCE VOMITING.

Never give anything by mouth to an unconscious person. Call a physician or Poison Control

Center immediately.

Notes to Physician Contains Denatured Ethyl Alcohol.

Ingestion may result in ethanol poisoning.

Treat symptomatically.

Protection of First-aiders Use personal protective equipment.

Aggravated Medical Conditions: NOTE TO PARENTS: Intentional misuse by deliberately concentrating and inhaling

aerosol products may be harmful or fatal. Help stop inhalation abuse; for information

visit www.inhalant.org.

5. FIRE-FIGHTING MEASURES

Flash point: 18.6°C (65.6°F)

FLAMMABLE AEROSOL.

Suitable Extinguishing Media: Use water spray, dry chemical, CO2, or "alcohol" foam as suitable for the surrounding fire

conditions.

Unsuitable Extinguishing media: No information available.

Specific Hazards Arising from the

Chemical:

Keep product and empty container away from heat and sources of ignition.

See Section 2 for Hazard Identification.

Unusual hazards: CONTENTS UNDER PRESSURE. Do not puncture or incinerate. Aerosol cans may

explode with extreme heat and become projectiles.

Special protective equipment for fire-

fighters

As in any fire, we ar self-contained breathing apparatus, pressure-demand, MSHA/NIOSH

(approved or equivalent) and full protective gear.

Precautions for fire-fighting Standard procedure for chemical fires. Move aerosol containers away from fire if possible

and safe to do so. Use water spray to cool fire exposed containers. Provide shielding to

protect firefighters from venting, rupturing or bursting containers.

NFPA Aerosol Level: Flammability Rating 1, per NFPA 30B.

NFPA: Health Hazard: 1 Flammability: 1 Instability / Reactivity 0 Special: --

HMIS: Health Hazard: 1 Flammability: 3 Physical Hazard: 0 Personal Protection: B

Key: (Also see Sections 3 & 8)



According to US Standard ANSI Z400.1-2004

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Ensure adequate ventilation.

Environmental Precautions: Do not allow material to contaminate ground water system. Local authorities should be

advised if significant spillages cannot be contained.

Methods for Cleaning Up: Small spills: Wearing appropriate protective equipment, soak up with an inert absorbent

material and dispose of in an appropriate waste container. Rinse surface residue and flush

to sink or sanitary sewer.

Large Spills: Eliminate all sources of ignition and ventilate the area with equipment rated for

use in flammable environments.

Collect any remaining liquid and store in metal container for later disposal according to

local, state, provincial or federal regulations.

Methods for Containment: Prevent further leakage or spillage if safe to do so.

HANDLING AND STORAGE

Handling: Use only as directed on the container label.

Ensure adequate ventilation

Wear personal protective equipment Avoid contact with skin, eyes and clothing

Avoid breathing vapors or mists Do not puncture or incinerate cans

Wash thoroughly with soap and water after handling.

Keep product and empty container away from heat and sources of ignition.

Storage: Store in original container in areas inaccessable to small children and pets.

Store in cool/well-ventilated place

CONTAINERS SHOULD BE KEPT OUT OF REACH OF CHILDREN.

Pressurised container. Protect from sunlight and do not expose to temperatures exceeding

55°C.

Do not pierce or burn after use. Keep away from all sources of ignition.

Fires involving flammable aerosols are severe and can spread very quickly. Warehouses and stores containing aerosols should therefore be separated from other areas by a fire

resistant construction of at least one half hour duration.

Stores should be well ventilated, particularily at low levels. The natural ventilation in a large

open warehouse building will normally be suitable.

Avoid the storage of aerosols in basesments where practicable.

This product must be stored and handled in accordance with the NFPA and local Fire Code

flammable liquids regulations.

EPA Registered Product: It is a violation of federal law to use this product in a manner inconsistent with its labeling.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name	ACGIH TLV	OSHA PEL
Ethanol	STEL: 1000 ppm	TWA: 1000 ppm
64-17-5		TWA: 1900 mg/m ³
n-butane	TWA: 1000 ppm	TWA: 1900 mg/m ³
106-97-8		TWA: 800 ppm



According to US Standard ANSI Z400.1-2004					
Propane 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m³			

Engineering Controls: For occupational exposures, ensure adequate ventilation.

Environmental exposure controls Local authorities should be advised if significant spillages cannot be contained

Personal Protective Equipment

Respiratory Protection: None required under normal usage.

Use only with adequate ventilation

Emergency responders should wear self-contained breathing apparatus (SCBA) to avoid inhalation of vapors generated by this product during a spill or other clean-up operations.

Eye/Face Protection: Avoid contact with eyes

Tightly fitting safety goggles

Hand Protection: Avoid contact with skin

Wear protective gloves/clothing

Skin and Body Protection: Usual safety precautions while handling the product will provide adequate protection against

injury or irritation. Follow product label instructions.

Hygiene Measures: Avoid contact with eyes, skin, and clothing.

Wash thoroughly with soap and water after handling.



According to US Standard ANSI Z400.1-2004

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:Liquid.Appearance:Aerosol

Colour: Clear

Odour: Characteristic of variant

pH 10.5 - 11.8

Flash Point: 18.6°C / 65.6°F (Concentrate)

Flammability Limits in Air: No information available

Autoignition Temperature: No information available.

Specific Gravity / Density [g/mL]: 0.8667 - 0.8967 @ 25°C (Concentrate)

Vapour Pressure: Not determined.

Solubility: Water solubility: completely soluble.

Explosion limits:

- upper: No data available.- lower: No data available.

10. STABILITY AND REACTIVITY

Stability: Stable under recommended storage conditions. Stable up to 55 °C.

Conditions to Avoid: Heat, flames and sparks.

Pressurised container. Protect from the sunlight and do not expose to temperatures exceeding 55°C (130°F). Extremes of temperature can occur in cars and near ovens and fireplaces. Do not place in contact with hot surfaces or near naked flames. Do not pierce or burn even after use. Do not spray on a naked flame, onto or near fire, or any incandescent

material such as an electric fire.

Materials to Avoid: Do not mix with other household chemicals.

Hazardous Decomposition Products: Oxides of carbon and unknown organic compounds.

Thermal decomposition can lead to release of irritating gases and vapors.

Polymerization: Hazardous polymerization does not occur.

Version No.:



According to US Standard ANSI Z400.1-2004

11. TOXICOLOGICAL INFORMATION

PRODUCT TOXICITY DATA

LD₅₀ Oral: No information available

LD₅₀ Dermal: No information available
 LC₅₀ Inhalation (Dust): No information available
 LC₅₀ Inhalation (Vapor): No information available

ACUTE EFFECTS

Eye Irritation Moderate eye irritation.

Skin Irritation None expected during normal conditions of use.

Inhalation None expected during normal use. However intentional misuse by deliberately

concentrating and inhaling the contents may be harmful or fatal.

Ingestion Contains denatured ethyl alcohol.

May be harmful if swallowed.

See Section 4 for First Aid instructions.

Sensitization Not expected to be a skin sensitiser.

Specific Effects

Carcinogenic Effects: Not listed as carcinogenic by OSHA, NTP or IARC.

Mutagenic Effects No information available.

Reproductive Toxicity: No information available.

Additional Toxicity Information: Information is based on available component data and toxicity result of similar products.

COMPONENT TOXICITY DATA

Chemical Name	CAS-No	LD50 Oral - with units - Rat - mg/kg	LD50 Dermal - With Units - Rat/Rabbit - mg/kg	LC50 Inhalation - With units - Rat/Rabbit
Ethanol	64-17-5	7060 mg/kg (Rat)		
n-butane	106-97-8			658 mg/L (Rat) 4 h
Propane	74-98-6			658 mg/L (Rat) 4 h



According to US Standard ANSI Z400.1-2004

12. ECOLOGICAL INFORMATION

PRODUCT TOXICITY DATA

Ecotoxicity effects

Aquatic toxicity: No information available

COMPONENT TOXICITY DATA

Ethanol

64-17-5 (30 - 60 %)

Freshwater Fish LC50 96 h Oncorhynchus mykiss 12.0-16.0 ml/L

LC50 96 h Pimephales promelas >100 mg/L

LC50 96 h Pimephales promelas 13400-15100 mg/L

Microtox EC50 = 35470 mg/L 5 min **Water Flea** LC50 48 h 9268 - 14221 mg/L

EC50 24 h 10800 mg/L EC50 48 h 2 mg/L

Other Information

Ozone depletion potential; ODP; No information available.

(R-11 = 1)

Global Warming Potential (GWP): No information available.

Additional Ecological Information: Information given is based on data on the components and the

ecotoxicology of similar products.

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused

products:

Dispose of in accordance with local, state and federal regulations.

Contaminated Packaging: Do not re-use empty containers. DO NOT PUNCTURE OR INCINERATE! Dispose of

empty container in household trash.

Waste Disposal: Container disposal: Empty containers may be included with domestic refuse for disposal to a

landfill. This container may also be recycled in communities where aerosol container recycling is available. Before offering for recycling, empty the can or use the product

according to the label instructions.



According to US Standard ANSI Z400.1-2004

14. TRANSPORT INFORMATION

For long distance transport of bulk material or shrunk pallet take into consideration General remarks

sections 7 and 10.

DOT

Proper shipping name: Consumer Commodity

UN-No: UN1950 **Hazard Class** Not applicable **Subsidiary Class** Not applicable Packing group: Not applicable Reportable Quantity (RQ): Not applicable

Description: UN 1950, Aerosols, Class 2.1

Re-classed as Consumer Commodity ORM-D

Emergency Response Guide No:126 / 171

TDG

Proper shipping name: Consumer Commodity/LTD. QTY

UN-No: UN1950

Not applicable Packing group:

Description: UN 1950, Aerosols, Class 2.1

Re-classed as Consumer Commodity ORM-D

MEX Not applicable.

ICAO See IATA

IATA

UN-No: UN1950

Proper shipping name: Aerosols, flammable / Consumer Commodity **Hazard Class** 2.1 / (9 if shipped as a Consumer Commodity)

Subsidiary Class Not applicable Packing group: Not applicable

Description: UN1950, Aerosols, flammable, Limited Quantity or Consumer Commodity, ID8000 if

acceptable to airline.

See DG List. **Maximum quantity**

IMDG/IMO

Proper Shipping Name Aerosols **Hazard Class**

Subsidiary Risk:

Not applicable UN1950 **UN-No Packing Group** Not applicable **IMDG Page:** See IMDG Code. **Marine Pollutant** Not applicable F-D. S-U EmS: MFAG: Not applicable. Maximum quantity: See IMDG Code.

RID Not applicable.

ADR Not applicable.



According to US Standard ANSI Z400.1-2004

ADN Not applicable.

15. REGULATORY INFORMATION

Chemical Name	PICCS	TSCA	DSL	NDSL	ENCS	CHINA	AICS	EINECS/ ELINCS	South Africa STELs
Ethanol		Present	X		X	X	X	200-578-6	
n-butane		Present	X		Χ	Χ	X	203-448-7	
Propane		Present	X		X	X	X	200-827-9	

U.S. Regulations:

Ethanol - 64-17-5

NJRTK >

Appearance Colorless, clear, volatile liquid

SARA313 None

California Prop. 65 Developmental

n-butane - 106-97-8

NJRTK X

Appearance Colorless gas SARA313 None California Prop. 65 Not Listed

Propane - 74-98-6

NJRTK X

Appearance Colorless gas SARA313 None California Prop. 65 Not Listed

WHMIS (Canada)

WHMIS Hazard Class B5 Flammable aerosol



According to US Standard ANSI Z400.1-2004

16. OTHER INFORMATION

National Fire Protection Association (U.S.A.):



HMIS (U.S.A.):

Health Hazard	1
Flammability:	3
Physical hazards	0
Personal Protection	В

NFPA Aerosol Level: Flammability Rating 1, per NFPA 30B.

Reason for revision: Change of product name.

Additional advice: This product should only be used as directed on the label and for the purpose intended.

Prepared by: Reckitt Benckiser (U.S.) Inc.

Product Safety Department

1 Philips Parkway

Montvale, New Jersey 07646-1810 USA.

FAX: 201-476-7770

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.