Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 14.01.2015 Revision: 14.01.2015

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· **1.1 Product identifier**

· **Trade name: TopCat Once-A-Day**

· **Article number:** 702

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.

· **Application of the substance / the mixture** Cleaner solvent

· **1.3 Details of the supplier of the Safety Data Sheet**

· **Manufacturer/Supplier:**
Palmero Health Care
120 Goodwin Place
Stratford, CT 06615
Phone: (203) 377-6424
Email: customerservice@palmerohealth.com

· **1.4 Emergency telephone number:**
ChemTel Inc.
(800)255-3924, +1 (813)248-0585

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**
Classifications listed also are applicable to the OSHA GHS Hazard Communication Standard (29CFR1910.1200).
The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H361f, H411.
The following classifications are applicable only to OSHA (USA) regulations and not the specific CLP regulation: H280, H361.


GHS 04 gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.


flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.


health hazard

Repr. 2	H361f	Suspected of damaging fertility.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 2)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 14.01.2015 Revision: 14.01.2015

Trade name: TopCat Once-A-Day

(Contd. of page 1)


environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

· **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**


Xn; Harmful

R48/20-62-65: Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of impaired fertility. Harmful: may cause lung damage if swallowed.


Xi; Irritant

R38: Irritating to skin.


F+; Extremely flammable

R12: Extremely flammable.


N; Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67: Vapours may cause drowsiness and dizziness.

· **Information concerning particular hazards for human and environment:**
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
Warning! Pressurised container.

· **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.
The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**
The following classifications are applicable only to OSHA (USA) regulations and not the specific CLP regulation: H280, H304, H361.
The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H361f, H411.
The product is additionally classified and labelled according to the Globally Harmonized System within the United States (GHS).
The product is classified and labelled according to the CLP regulation.

(Contd. on page 3)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 14.01.2015 Revision: 14.01.2015

Trade name: TopCat Once-A-Day

(Contd. of page 2)

· **Hazard pictograms**



This pictogram only applicable for EU regulations. Not for use in the United States (OSHA GHS).

The following pictograms are only for use within the United States (OSHA): GHS04.



GHS 04 gas cylinder



GHS02 GHS07 GHS08 GHS09

· **Signal word** Danger

· **Hazard-determining components of labelling:**
n-hexane

· **Hazard statements**
The following Hazard Statements are applicable only according to OSHA regulations within the United States. These Statements are not applicable for the CLP regulation (1272/2008/EC) in the EU: H280, H304, H361.
The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H361f.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways
Repr. 2 H361: Suspected of damaging fertility or the unborn child.
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H315 Causes skin irritation.
H361f Suspected of damaging fertility.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P251 Pressurized container: Do not pierce or burn, even after use.
P211 Do not spray on an open flame or other ignition source.
P280 Wear protective gloves / eye protection.
P202 Do not handle until all safety precautions have been read and understood.
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 4)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 14.01.2015 Revision: 14.01.2015

Trade name: TopCat Once-A-Day

(Contd. of page 3)

· **Hazard description:**
· **WHMIS-symbols:**
B5 - Flammable aerosol
D2A - Very toxic material causing other toxic effects



· **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 4
Reactivity = 3

· **HMIS-ratings (scale 0 - 4)**



Health = *2
Fire = 4
Reactivity = 3

* - Indicates a long term health hazard from repeated or prolonged exposures.

· **HMIS Long Term Health Hazard Substances**	
110-54-3	n-hexane

· **2.3 Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable.
· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**
· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**		
CAS: 110-54-3 EINECS: 203-777-6 Index number: 601-037-00-0	n-hexane Xn R48/20-62-65; Xi R38; F R11; N R51/53 R67 Repr. Cat. 3 Flam. Liq. 2, H225 Repr. 2, H361f; STOT RE 2, H373; Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336	25-50%

(Contd. on page 5)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 14.01.2015 Revision: 14.01.2015

Trade name: TopCat Once-A-Day

(Contd. of page 4)

CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5	propane F+ R12 Flam. Gas 1, H220 Press. Gas C, H280	10-25%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0	isobutane F+ R12 Flam. Gas 1, H220 Press. Gas C, H280	10-25%
CAS: 64742-54-7 EINECS: 265-157-1 Index number: 649-467-00-8	Distillates (petroleum), hydrotreated heavy paraffinic Carc. 1B, H350	25-50%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**
· **General information:**
Take affected persons out into the fresh air.
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
· **After inhalation:**
Supply fresh air; consult doctor in case of complaints.
Provide oxygen treatment if affected person has difficulty breathing.
In case of unconsciousness place patient stably in side position for transportation.
· **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
· **After eye contact:**
Protect unharmed eye.
Remove contact lenses if worn.
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
· **After swallowing:**
Unlikely route of exposure.
Rinse out mouth and then drink plenty of water.
Do not induce vomiting; call for medical help immediately.
A person vomiting while laying on their back should be turned onto their side.
· **4.2 Most important symptoms and effects, both acute and delayed**
Headache
Breathing difficulty
Dizziness
Coughing
Irritant to skin and mucous membranes.
Nausea in case of ingestion.
May cause gastro-intestinal irritation if ingested.
· **Hazards**
Vapours may cause drowsiness and dizziness.

(Contd. on page 6)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 14.01.2015 Revision: 14.01.2015

Trade name: TopCat Once-A-Day

(Contd. of page 5)

Danger of pneumonia.
May cause neurotoxic effects.
Danger of pulmonary oedema.
Danger of impaired breathing.
Suspected of damaging fertility or the unborn child.

· **4.3 Indication of any immediate medical attention and special treatment needed**
If swallowed, gastric irrigation with added, activated carbon.
Contains Hexane.
Later observation for pneumonia and pulmonary oedema.
If necessary oxygen respiration treatment.
If swallowed or in case of vomiting, danger of entering the lungs.
Medical supervision for at least 48 hours.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**
· **Suitable extinguishing agents:** CO2, sand, extinguishing powder. Do not use water.
· **For safety reasons unsuitable extinguishing agents:** Water
· **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
Danger of receptacles bursting because of high vapour pressure when heated.
· **5.3 Advice for firefighters**
· **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
· **Additional information**
Eliminate all ignition sources if safe to do so.
Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
Cool endangered receptacles with water fog or haze.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**
Use respiratory protective device against the effects of fumes/dust/aerosol.
Ensure adequate ventilation
Wear protective equipment. Keep unprotected persons away.
Remove ignition sources.
Protect from heat.
· **6.2 Environmental precautions:**
Do not allow to enter sewers/ surface or ground water.
Inform respective authorities in case of seepage into water course or sewage system.
· **6.3 Methods and material for containment and cleaning up:**
Allow to evaporate.
Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).
Ensure adequate ventilation.
Dispose contaminated material as waste according to item 13.
Send for recovery or disposal in suitable receptacles.

(Contd. on page 7)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 14.01.2015 Revision: 14.01.2015

Trade name: TopCat Once-A-Day

(Contd. of page 6)

Do not flush with water or aqueous cleansing agents

· **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**
Use only in well ventilated areas.
Do not spray on flame or other ignition sources. No smoking.
Avoid splashes or spray in enclosed areas.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

· **Information about fire - and explosion protection:**
Flammable aerosol.
Keep ignition sources away - Do not smoke.
Keep respiratory protective device available.
Protect against electrostatic charges.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
Do not spray onto a naked flame or any incandescent material.
Emergency cooling must be available in case of nearby fire.

· **7.2 Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:**
Avoid storage near extreme heat, ignition sources or open flame.
Provide ventilation for receptacles.
Observe official regulations on storing packagings with pressurised containers.
· **Information about storage in one common storage facility:**
Store away from foodstuffs.
Store away from oxidising agents.
· **Further information about storage conditions:**
Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.
· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**	
110-54-3 n-hexane	
IOELV (EU)	Long-term value: 72 mg/m³, 20 ppm
PEL (USA)	Long-term value: 1800 mg/m³, 500 ppm

(Contd. on page 8)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 14.01.2015 Revision: 14.01.2015

Trade name: TopCat Once-A-Day

(Contd. of page 7)

REL (USA)	Long-term value: 180 mg/m³, 50 ppm
TLV (USA)	Long-term value: 176 mg/m³, 50 ppm Skin; BEI
EL (Canada)	Long-term value: 20 ppm Skin
EV (Canada)	Long-term value: 176 mg/m³, 50 ppm
74-98-6 propane	
PEL (USA)	Long-term value: 1800 mg/m³, 1000 ppm
REL (USA)	Long-term value: 1800 mg/m³, 1000 ppm
TLV (USA)	refer to Appendix F
EL (Canada)	Long-term value: 1000 ppm
EV (Canada)	Long-term value: 1,000 ppm
75-28-5 isobutane	
TLV (USA)	Short-term value: 2370 mg/m³, 1000 ppm
EV (Canada)	Long-term value: 800 ppm

· **DNELs** No further relevant information available.
· **PNECs** No further relevant information available.

· **Ingredients with biological limit values:**	
110-54-3 n-hexane	
BEI (USA)	0,4 mg/L Medium: urine Time: end of shift at end of workweek Parameter: 2,5-Hexanedione without hydrolysis

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**
· **Personal protective equipment:**
· **General protective and hygienic measures:**
The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
· **Respiratory protection:** Suitable respiratory protective device recommended.
· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.
· **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several

(Contd. on page 9)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 14.01.2015 Revision: 14.01.2015

Trade name: TopCat Once-A-Day

(Contd. of page 8)

substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact gloves made of the following materials are suitable:**
Nitrile rubber, NBR
Neoprene gloves

· **Eye protection:**



Safety glasses

· **Body protection:** Solvent resistant protective clothing

· **Limitation and supervision of exposure into the environment** Avoid release to the environment.

· **Risk management measures**
See Section 7 for additional information.
No further relevant information available.

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Liquid
Colour:	Clear to straw color.
· **Odour:**	Solvent-like
· **Odour threshold:**	Not determined.
· **pH-value:**	Not determined.
· **Change in condition**	
Melting point/Melting range:	Not applicable, as aerosol.
Boiling point/Boiling range:	Not applicable, as aerosol.
· **Flash point:**	Not applicable, as aerosol.
· **Flammability (solid, gaseous):**	Extremely flammable aerosol.
· **Auto/Self-ignition temperature:**	Not determined.
· **Decomposition temperature:**	Not determined.
· **Self-igniting:**	Product is not self-igniting.
· **Danger of explosion:**	Risk of explosion if heated under confinement.
· **Density at 20 °C:**	.77 g/cm³
· **Relative density**	Not determined.
· **Vapour density**	Not determined.
· **Evaporation rate**	Not applicable.

(Contd. on page 10)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 14.01.2015 Revision: 14.01.2015

Trade name: TopCat Once-A-Day

(Contd. of page 9)

· **Solubility in / Miscibility with water:** Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**
Dynamic: Not determined.
Kinematic: Not determined.

· **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

· **10.1 Reactivity**
· **10.2 Chemical stability**
· **Thermal decomposition / conditions to be avoided:**
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Danger of receptacles bursting because of high vapour pressure when heated.
Pressurized container: Do not pierce or burn, even after use.
· **10.3 Possibility of hazardous reactions**
Extremely flammable aerosol.
Danger of receptacles bursting because of high vapour pressure when heated.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.
Used empty containers may contain product gases which form explosive mixtures with air.
Toxic fumes may be released if heated above the decomposition point.
· **10.4 Conditions to avoid**
Keep ignition sources away - Do not smoke.
Store away from oxidising agents.
· **10.5 Incompatible materials:** Oxidizing agents
· **10.6 Hazardous decomposition products:**
Under fire conditions only:
Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

· **11.1 Information on toxicological effects**
· **Acute toxicity:**
· **Primary irritant effect:**
· **on the skin:** Irritant to skin and mucous membranes.
· **on the eye:** No irritating effect.
· **Sensitisation:** No sensitising effects known.
· **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant
Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.
May cause cancer.

(Contd. on page 11)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 14.01.2015 Revision: 14.01.2015

Trade name: TopCat Once-A-Day

(Contd. of page 10)

Suspected of damaging fertility or the unborn child.
Causes damage to organs.
· **Acute effects (acute toxicity, irritation and corrosivity):**
The product can cause inheritable damage.
Vapours have narcotic effect.
Carcinogenic.
May be harmful if swallowed or if inhaled.
· **Repeated dose toxicity:**
May cause neurotoxic effects.
May cause damage to organs through prolonged or repeated exposure.
· **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):**
Repr. 2

SECTION 12: Ecological information

· **12.1 Toxicity**
· **Aquatic toxicity:** Toxic for aquatic organisms
· **12.2 Persistence and degradability** No further relevant information available.
· **12.3 Bioaccumulative potential** No further relevant information available.
· **12.4 Mobility in soil** No further relevant information available.
· **Ecotoxical effects:**
· **Remark:** Toxic for fish
· **Additional ecological information:**
· **General notes:**
Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
Toxic for aquatic organisms
Also poisonous for fish and plankton in water bodies.
Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.
· **12.5 Results of PBT and vPvB assessment**
· **PBT:** Not applicable.
· **vPvB:** Not applicable.
· **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**
· **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Incinerate in accordance with local, state and federal regulations.
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

(Contd. on page 12)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 14.01.2015 Revision: 14.01.2015

Trade name: TopCat Once-A-Day

(Contd. of page 11)

· **Uncleaned packaging:**
· **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· **14.1 UN-Number**
· **DOT, ADR, IMDG, IATA** UN1950
· **14.2 UN proper shipping name**
· **DOT, IMDG, IATA** 1950 AEROSOLS, N.O.S., FLAMMABLE
· **ADR** 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
· **14.3 Transport hazard class(es)**
· **DOT**



· **Class** 2.1
· **Label** 2.1

· **ADR**



· **Class** 2.1 5F
· **Label** 2.1

· **IMDG, IATA**



· **Class** 2.1
· **Label** 2.1
· **14.4 Packing group** Not regulated for transport.
· **DOT, ADR, IMDG, IATA** Not Regulated
· **14.5 Environmental hazards:**
· **Marine pollutant:** No
· **14.6 Special precautions for user** Not applicable.
· **EMS Number:** F-D,S-U
· **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

(Contd. on page 13)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 14.01.2015 Revision: 14.01.2015

Trade name: TopCat Once-A-Day

(Contd. of page 12)

· **Transport/Additional information:**

· **ADR**	
· **Limited quantities (LQ)**	1L
· **Excepted quantities (EQ)**	Code: E0 Not permitted as Excepted Quantity
· **Tunnel restriction code**	D
· **IMDG**	
· **Limited quantities (LQ)**	1L
· **Excepted quantities (EQ)**	Code: E0 Not permitted as Excepted Quantity
· **UN "Model Regulation":**	UN1950, AEROSOLS, ENVIRONMENTALLY HAZARDOUS, 2.1

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
· **United States (USA)**
· **SARA**

· **Section 355 (extremely hazardous substances):**
None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

110-54-3	n-hexane

· **TSCA (Toxic Substances Control Act):**
All ingredients are listed.

· **Proposition 65 (California):**

· **Chemicals known to cause cancer:**
None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**
None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**
None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**
None of the ingredients are listed.

· **Carcinogenic Categories**

· **EPA (Environmental Protection Agency)**

110-54-3	n-hexane	II

· **IARC (International Agency for Research on Cancer)**
None of the ingredients are listed.

· **TLV (Threshold Limit Value established by ACGIH)**
None of the ingredients are listed.

(Contd. on page 14)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 14.01.2015 Revision: 14.01.2015

Trade name: TopCat Once-A-Day

(Contd. of page 13)

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients are listed.

· **Canada**

· **Canadian Domestic Substances List (DSL)**

All ingredients are listed.

· **Canadian Ingredient Disclosure list (limit 0.1%)**

None of the ingredients are listed.

· **Canadian Ingredient Disclosure list (limit 1%)**

110-54-3	n-hexane

· **Other regulations, limitations and prohibitive regulations**
This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

· **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients are listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**
H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H350 May cause cancer.
H361f Suspected of damaging fertility.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

R11 Highly flammable.
R12 Extremely flammable.
R38 Irritating to skin.
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R62 Possible risk of impaired fertility.
R65 Harmful: may cause lung damage if swallowed.
R67 Vapours may cause drowsiness and dizziness.

· **Abbreviations and acronyms:**
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation

(Contd. on page 15)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 14.01.2015 Revision: 14.01.2015

Trade name: TopCat Once-A-Day

(Contd. of page 14)

IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
WHMIS: Workplace Hazardous Materials Information System (Canada)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
Flam. Gas 1: Flammable gases, Hazard Category 1
Flam. Aerosol 1: Flammable aerosols, Hazard Category 1
Press. Gas C: Gases under pressure: Compressed gas
Flam. Liq. 2: Flammable liquids, Hazard Category 2
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Carc. 1B: Carcinogenicity, Hazard Category 1B
Repr. 2: Reproductive toxicity, Hazard Category 2
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2
Asp. Tox. 1: Aspiration hazard, Hazard Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

· **Sources**

SDS Prepared by:
ChemTel Inc.
1305 North Florida Avenue
Tampa, Florida USA 33602-2902
Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573
Website: www.chemtelinc.com