



SAFETY DATA SHEET

Alginate Impression Materials

Section 1. Identification

GHS product identifier

: Alginate Impression Materials

Other means of identification

: Identic Dust Free, Image, Kromafaze

Product type

: Powder.

Relevant identified uses of the substance or mixture and uses advised against

Product use

: Dental product: Impression material.

Area of application

: Professional applications.

Manufacturer

: DUX DENTAL Inc. 600 E. Hueneme Road Oxnard, CA 93033

Telephone no.: 805-488-1122 or 800-833-8267

Fax no.: 800-444-5170 www.duxdental.com

e-mail address of person responsible for this SDS

: Contact customer service at 1-800-KERR-123 for any questions

Emergency telephone number (with hours of operation)

: CHEMTREC® (24 hours) U.S.: 1-800-424-9300

International: +1-703-527-3887

Section 2. Hazards identification

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Health effects are based on the uncured material.

Classification of the substance or mixture

: EYE IRRITATION - Category 2A CARCINOGENICITY - Category 1A

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (bones, lungs and

teeth) - Category 1

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 78%

GHS label elements

Hazard pictograms





Signal word

Danger

Section 2. Hazards identification

Hazard statements

: Causes serious eye irritation.

May cause cancer.

Causes damage to organs through prolonged or repeated exposure. (bones, lungs,

Precautionary statements

Prevention

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Do not breathe dust or mist. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.

Response

: Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Storage

: Store locked up.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and

international regulations.

Hazards not otherwise classified

Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat.

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Other means of identification

: Identic Dust Free, Image, Kromafaze

CAS number/other identifiers

CAS number

Not applicable.

Product code

: 27098, 27434, 27456, 27475, 27477, 27487, 27488, 27457, 27481, 27484, 27495, 27492, 27493, 27412, 27416, 27417, 27419, 27460, 27426, 27427, 27429, 27461,

27444, 27452, 27467, 27453, 27497

Ingredient name	Other names	%	CAS number
cristobalite Alginic acid, potassium salt crystalline silica respirable dipotassium hexafluorotitanate	Not available. Not available. Not available. Not available.	30-60 10-30 1-5 1-5	14464-46-1 9005-36-1 14808-60-7 16919-27-0

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: No special measures are required. In case of contact with eyes, rinse immediately with plenty of water. Get medical attention if symptoms occur.

Inhalation

: No special measures required. If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Skin contact

: No special measures required. In case of contact, immediately flush skin with plenty of

water. Get medical attention if symptoms occur.

Date of issue/Date of revision

: 08/03/2015 Date of previous issue

No previous validation

Version :1

Section 4. First aid measures

Ingestion

: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Get medical attention if adverse health effects persist or are severe.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact

: Causes serious eye irritation.

Inhalation

: Exposure to airborne concentrations above statutory or recommended exposure limits

may cause irritation of the nose, throat and lungs.

Skin contact

: No known significant effects or critical hazards.

Ingestion

: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact

: Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation

: Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact

: No specific data.

Ingestion

: No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments

: No specific treatment.

Protection of first-aiders

: In case of major fire and large quantities: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: Do not use water jet.

Specific hazards arising from the chemical

: No specific fire or explosion hazard.

Date of issue/Date of revision

: 08/03/2015

Date of previous issue

: No previous validation

Version :1

Section 5. Fire-fighting measures

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides sulfur oxides

halogenated compounds metal oxide/oxides Fluoride compounds

Special protective actions for fire-fighters

In case of major fire and large quantities: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: Low release. For professional use only. Handling of product in very small amounts or in situations where release is highly unlikely

For emergency responders: Low release. See also the information in "For non-emergency personnel".

Environmental precautions

: Low release. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Small Quantity. For professional use only. Absorb with an inert material and place in an appropriate waste disposal container.

Large spill

: Small Quantity. For professional use only. Absorb with an inert material and place in an appropriate waste disposal container.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

No special measures are required for small quantities under normal and intended conditions of product use. For professional use only. Put on appropriate personal protective equipment (see Section 8). Handle with care and dispose in a safe manner.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Date of issue/Date of revision

: 08/03/2015

Date of previous issue

*No previous validation

Version :1

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
cristobalite	OSHA PEL Z3 (United States, 2/2013).
onstobalito	Notes: 1/2[250/(%SiO2+5)]
	TWA: 250 MPPCF / 2 x (%SiO2+5) 8 hours.
	Form: Respirable
	OSHA PEL Z3 (United States, 2/2013).
	Notes: 1/2[10/(%SiO2+2)]
	TWA: 10 MG/M3 / 2 x (%SiO2+2) 8 hours.
	Form: Respirable
	OSHA PEL 1989 (United States, 3/1989).
	TWA: 0.05 mg/m³, (as quartz) 8 hours. Form:
	Respirable dust
	ACGIH TLV (United States, 4/2014).
	TWA: 0.025 mg/m ³ 8 hours. Form:
	Respirable fraction
	NIOSH REL (United States, 10/2013).
	TWA: 0.05 mg/m³ 10 hours. Form: respirable
	dust
	OSHA PEL Z3 (United States, 2/2013).
	Notes: 1/2[30/(%SiO2+2)]
	TWA: 30 MG/M3 / 2 x (%SiO2+2) 8 hours.
	Form: Total dust
crystalline silica respirable	OSHA PEL Z3 (United States, 2/2013).
	TWA: 250 MPPCF / (%SiO2+5) 8 hours.
	Form: Respirable
	TWA: 10 MG/M3 / (%SiO2+2) 8 hours. Form:
	Respirable
	OSHA PEL 1989 (United States, 3/1989).
	TWA: 0.1 mg/m³, (as quartz) 8 hours. Form:
	Respirable dust
	ACGIH TLV (United States, 4/2014).
	TWA: 0.025 mg/m³ 8 hours. Form:
	Respirable fraction
	NIOSH REL (United States, 10/2013).
	TWA: 0.05 mg/m³ 10 hours. Form: respirable
	dust

Appropriate engineering controls

Environmental exposure controls

No special measures are required for small quantities under normal and intended conditions of product use.

: No special measures are required for small quantities under normal and intended conditions of product use.

Individual protection measures

Hygiene measures

: No special measures are required for small quantities under normal and intended conditions of product use.

Date of issue/Date of revision

: 08/03/2015

Date of previous issue

: No previous validation

Version :1

Section 8. Exposure controls/personal protection

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. If operating conditions cause high dust concentrations to be produced, use dust goggles.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: No special measures are required for small quantities under normal and intended conditions of product use.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: No special measures are required for small quantities under normal and intended conditions of product use.

Section 9. Physical and chemical properties

Pleasant.

Appearance

Odor

Physical state : Solid. [Powder.]

Color : Various

Odor threshold : Not available.

pH : Not available.

Melting point : Not available.

Boiling point : Not available.

Flash point : Not available.

Evaporation rate : Not available.
Flammability (solid, gas) : Not applicable.

Lower and upper explosive

(flammable) limits

Not available.

Vapor pressure : Not available.
Vapor density : Not available.
Relative density : Various

Solubility : Various

Solubility in water : Not available.

Partition coefficient: n-octanol/water

: Not available.

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

SADT : Not available.

Viscosity : Various

Date of issue/Date of revision

: 08/03/2015

Date of previous issue

: No previous validation

Version :1

Section 10. Stability and reactivity

Reactivity

: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability

The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Under normal conditions of storage and use, hazardous polymerization will not occur.

Conditions to avoid

: Elevated temperature

Incompatible materials

: Reactive or incompatible with the following materials: acids.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Not available.

Irritation/Corrosion

Not available.

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP	
cristobalite	2	1	Known to be a human carcinogen.	
crystalline silica respirable	2	1	Known to be a human carcinogen.	

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Date of issue/Date of revision 08/03/2015 Date of previous issue No previous validation Version :1 7/12

Section 11. Toxicological information

Name	Category	Route of exposure	Target organs
cristobalite	Category 1	Inhalation	lungs
crystalline silica respirable	Category 1	Inhalation	lungs
dipotassium hexafluorotitanate	Category 2	Not determined	bones and teeth

Aspiration hazard

Not available.

Information on the likely

routes of exposure

: Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential acute health effects

Eye contact

: Causes serious eye irritation.

Inhalation

: Exposure to airborne concentrations above statutory or recommended exposure limits

may cause irritation of the nose, throat and lungs.

Skin contact Ingestion

No known significant effects or critical hazards.No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact

: Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation

: Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact Ingestion No specific data.No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

otentiai iminediate

: Not available.

effects

Potential delayed effects

: Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects

: Not available.

Potential chronic health effects

Not available.

Conclusion/Summary

: Breathing excessive silica dust for a long time can cause silicosis.

General

: Causes damage to organs through prolonged or repeated exposure. Repeated or

prolonged inhalation of dust may lead to chronic respiratory irritation.

Carcinogenicity

: May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity

No known significant effects or critical hazards.

Teratogenicity

: No known significant effects or critical hazards.

Date of issue/Date of revision

: 08/03/2015

Date of previous issue

No previous validation

Version :1

Alginate Impression Materials

Section 11. Toxicological information

Developmental effects

: No known significant effects or critical hazards.

Fertility effects

: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	17739.8 mg/kg

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Section 14. Transport information

	DOT Classification	IMDG	IATA			
UN number	Not regulated.	Not regulated.	Not regulated.			
UN proper shipping name	-	· ·	—			
Transport hazard class(es)	T.	## ***********************************				
Packing group	-	-	н:			

Date of issue/Date of revision

: 08/03/2015

Date of previous issue

: No previous validation

Version : 1

Alginate Impression Materials

Section 14. Transport information

Environmental hazards	No.	No.	No.
Additional information	-	-	-

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to Annex II of MARPOL

Section 15. Regulatory information

U.S. Federal regulations

73/78 and the IBC Code

: United States inventory (TSCA 8b): All components are listed or exempted.

Clean Water Act (CWA) 307: polychloro copper phthalocyanine; Boron zinc hydroxide

oxide

Clean Water Act (CWA) 311: trisodium orthophosphate; Formaldehyde; Boron zinc

hydroxide oxide

Clean Air Act Section 112

(b) Hazardous Air Pollutants (HAPs) : Not listed

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

Class II Substances

: Not listed

DEA List I Chemicals

(Precursor Chemicals)

: Not listed

: Not listed

DEA List II Chemicals

(Essential Chemicals)

SARA 302/304

Composition/information on ingredients

			SARA 302 TPQ		SARA 304 RQ	
Name	%	EHS	(lbs)	(gallons)	(lbs)	(gallons)
Formaldehyde	<0.000175	Yes.	500	73.9	100	14.8

SARA 304 RQ

: 63492063.5 lbs / 28825396.8 kg

SARA 311/312

Classification

Immediate (acute) health hazard Delayed (chronic) health hazard

Composition/information on ingredients

Date of issue/Date of revision

: 08/03/2015

Date of previous issue

; No previous validation

Version :1

Section 15. Regulatory information

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
cristobalite Alginic acid, potassium salt crystalline silica respirable dipotassium hexafluorotitanate	30-60 10-30 1-5 1-5	No. No. No.	No. No. No.	No. No. No. No.	No. Yes. No. Yes.	Yes. No. Yes. Yes.

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	Boron zinc hydroxide oxide	138265-88-0	1-5
Supplier notification	Boron zinc hydroxide oxide	138265-88-0	1-5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts

: The following components are listed: SILICA, CRYSTALLINE, QUARTZ;

CRISTOBALITE DUST

New York

: None of the components are listed.

New Jersey

: The following components are listed: COPPER compounds; GYPSUM; SILICA,

QUARTZ; QUARTZ (SiO2); ZINC compounds; SILICA, CRISTOBALITE;

CRISTOBALITE (SiO2)

Pennsylvania

: The following components are listed: COPPER COMPOUNDS; GYPSUM (CA(SO4). 2H2O); QUARTZ (SIO2); ZINC COMPOUNDS; CRISTOBALITE (SIO2); SILICA

AMORPHOUS DIATOMACEOUS EARTH (UNCALCINED)


California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer-

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
cristobalite	Yes.	No.	No.	No.
crystalline silica respirable	Yes.	No.	No.	No.
Formaldehyde	Yes.	No.	Yes.	No.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

Date of issue/Date of revision

: 08/03/2015

Date of previous issue

*No previous validation

Version :1

Section 16. Other information

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)

Flammability Instability/Reactivity Special

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

History

Date of issue/Date of

revision

Date of previous issue

: No previous validation

Version

. 08/03/2015

Key to abbreviations

: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

References

: HCS (U.S.A.)- Hazard Communication Standard

International transport regulations

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot quarantee that these are the only hazards that exist.