Identity (As Used on Label and List):	Manufacturer's Product:	
COPALITE® SOLVENT/THINNER	4000-03	Revised MSDS: Jan
	11	, 2010

SECTION I - PRODUCT IDENTIFICATION AND USE			
Manufacturer's Name:	Information Telephone Number:		
COOLEY & COOLEY, LTD.	281-897-0009		
Address (Number, Street, City, State Zip Code, and Country):	Emergency Telephone Number:		
8550 WESTLAND WEST BLVD.	1-800-535-5053 (USA)		
HOUSTON, TX 77041	(INFOTRAC)		
U.S.A.	1-352-323-3500 (International)		
	(FOR CHEMICAL EMERGENCY		
	ONLY)		

SECTION II				
Hazardous Components (Specific Chemical Identity: Common Name(s): CAS #	OSHA PEL	ACGIH TLV	WHMIS	%
BLENDED INGREDIENTS:				
ETHYL ETHER ANYDROUS 60- 29-7	400PPM	500PPM	Class B	
CHLOROFORM 67- 66-3	50PPM	50PPM	Class D/Div.1	
FLAMMABLE LIQUIDS N.O.S., CLASS #3, Packing Group II, UN #1993 Health : 2-Hazardous				
Specific Hazard: Blank, Fire: 4-Store below 73° F Reactivity: 1- Unstable if heated				

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS			
Boiling Point:	Specific Gravity (H20-1):		
34° ± 4°C	1-1.474 – 1.478		
Vapor Pressure (mm Hg.):	Melting Point:		
760MM	N/A LIQUID FORM		
Vapor Density (Air=1):	Evaporation Rate:		
25% 1.471	(BUTYL ACETATE=1) 2.2		
Solubility in Water:	Appearance and Odor:		
INSOLUBLE	CLEAR COLOR; SWEET ODOR		

SECTION IV – FIRE AND EXPLOSION HAZARD DATA					
Flash Point (Method used):	Flammable Limits:	LEL	UEL		
75°F ± 5°F ASTM TAG OPEN CUP 65°F 75°F					
Extinguishing Media:					
FIRE EXTINGUISHER A, B & C CLASSIFICATION					

Special Fire Fighting Procedures:
PUT ON GAS MASK. AIM THE FIRE EXTINGUISHER AT THE BASE OF THE
FLAME.
Unusual Fire and Explosion Hazards:
ETHER IS VOLATILE. CO2 AND CO ARE GASES PRODUCED DURING A HIGH HEAT FIRE.
GAS MASK AND FIRE EXTINGUISHER ARE NECESSARY TO PUT OUT FIRE.

SECTION V - REACTIVITY DATA				
Stability:	Unstable:	Conditions	to Avoid:	
	ABOVE 75°F	AVOID EXCESSIVE EXPOSURE TO HIGH		
	Stable:] HEAT/F	EAT/FLAMES.	
	65°F	1		
Incompatibility (Material	s to Avoid):			
WATER				
Hazardous Decomposition or Byproducts:				
CHLOROFORM				
Hazardous Polymerization: May O		ccur:	Conditions to Avoid:	
	>	(MELTS SOFT PLASTIC	
	Will Not	Occur:	MATERIAL. WILL NOT MELT OR SOFTEN HARDER GRADE	
	>	(PLASTICS.	

SECTION VI – HEALTH HAZARD DATA				
Route(s) of Entry:	Inhalation?	Skin?	Ingestion?	
	X		X	
Health Hazards (Acute & Chr	onic):			
INHALATION:	ACUTE DIFFICULTY I	N BREATHING, CHROI	NIC LUNG	
DISEASE PER	SONS SHOULD LIMIT	EXPOSURE.		
SKIN: ACUTE	- CLEAN AREA WITH	ISOPROPYL ALCOHOL	L; CHRONIC –	
UNKNOWN.				
INGESTION: I	NDUCE VOMITING WI	TH IPECAC SYRUP AC	CORDING TO	
DIRECTIONS.				
Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?	
N/A	N/A	N/A	YES	
CHLOROFORM	M IS A KNOWN CARCI	NOGEN TO LABORATO	ORY RATS IN	
EXTREME CAS	SES.			
Signs and Symptoms of Expo	sure:			
DIFFICULTY IN BREATHING, TIGHTNESS IN CHEST DUE TO				
CONSTRICTION OF BRONCHIOLES.				
Medical Conditions Generally Aggravated by Exposure:				
DISEASES OF THE LUNGS, EMPHYSEMA, ASTHMA, TUBERCULOSIS,				
PNUEMONIA, PLEURASY.				
Emergency and First Aid Procedures:				
VENTILATE AREA. MOVE PERSON(S) TO FRESH AIR.				
EYE CONTACT: FLUSH WITH WATER FOR 15 MINUTES, OR USE EYEWASH,				
AND CALL AN	AND CALL AN OPTHALMOLOGIST.			

SECTION VII- PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken In Case Material is Released or Spilled:

SPILLS: VENTILATE AREA, EXIT ALL PERSONS UNTIL AROMA DISSIPATES. CLEAN AREA UP WITH ISOPROPYL ALCOHOL.

RELEASE OF FUMES: REMOVE ALL PERSONS, VENTILATE AREA UNTIL AROMA DISSIPATES.

Waste Disposal Method:

DISPOSE AS HAZARDOUS MATERIAL, BY INCINERATION ACCORDING TO OSHA REGULATIONS.

Precautions To Be Taken In Handling and Storing:

DUE TO EVAPORATION, KEEP BOTTLE TIGHTLY CAPPED WHEN NOT IN USE. STORE IN A COOL, DRY PLACE.

Other Precautions:

THIS PRODUCT IS FOR PROFESSIONAL USE ONLY AS STATED IN THE DIRECTIONS. IT IS THE RESPONSIBILITY OF THE DENTIST TO TRAIN HIS AUXILIARY PERSONNEL IN THE SAFE USE, STORAGE AND FIRST AID PROCEDURES.

SECTION V	/III-CONTROL MEASURES			
Respiratory Pro	tection (Specify Type):			
RES	PIRATOR OR MASK USED FOR	R PROT	ECTION AGAINST ORGANIC	
VAP	ORS.			
Ventilation :	Local Exhaust:		Special:	
	OPEN WINDOWS, EXH	IAUST	EXIT AREA	
	FANS			
	Mechanical (General):		Other:	
	VENT HOODS (INDUSTRIAL			
	TYPE)			
Protective Glov	es:	Eye Prote	ection:	
LATEX			SAFETY GLASSES/GOGGLES	
Other Protective	e Clothing or Equipment:			
LAB	COAT			
Work/Hygienic I	Practices:			

MAINTAIN ASEPSIS. DO NOT PLACE CONTAMINATED INSTRUMENTS INTO BOTTLE OF SOLVENT.