

Material Safety Data Sheet
May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072



IDENTITY (As Used on Label and List)
LUXATEMP AUTOMIX

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that

Section I

Manufacturer's Name

DMG

Address (Number, Street, City, State, and ZIP Code)

Elbgastr 248

22531 Hamburg 53

Germany

Emergency Telephone Number

201-894-5500 (800-662-6383)

Telephone Number for Information

201-894-5500 (800-662-6383)

Date Prepared

1/93

Signature of Preparer (optional)

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))

OSHA PEL

ACGIH TLV

Other Limits
Recommended

% (optional)

glycol methacrylate

multifunctional acrylate

multifunctional methacrylate

malonylurea derivative

Section III — Physical/Chemical Characteristics

Boiling Point

n.a.

Specific Gravity ($H_2O = 1$)

1.4

Vapor Pressure (mm Hg.)

negligible

Melting Point

n.a.

Vapor Density (AIR = 1)

> 1

Evaporation Rate
(Butyl Acetate = 1)

< 1

Solubility in Water

< 5% wt/wt

Appearance and Odor

white-yellowish paste, odorless

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used)

> 100°C (DIN, ASTM)

Flammable Limits

LEL

n.a.

UEL

n.a.

Extinguishing Media

carbon dioxide, dry extinguishing media, foam

Special Fire Fighting Procedures

none

Unusual Fire and Explosion Hazards

polymerizes on heating, exothermally

